

SIMATIC S7-400, rack UR1 Alu, central and distributed with 18 slots, 2 redundant PS can be plugged in



Figure similar

| General information                               |          |
|---|----------|
| Product type designation                          | UR1      |
| Hardware configuration                            |          |
| Rack  |          |
| • Communication bus                               | Yes      |
| • P bus   | Yes      |
| Slots   |          |
| • Number of slots                                 | 18       |
| Standards, approvals, certificates                |          |
| CE mark   | Yes      |
| UKCA mark   | Yes      |
| UL approval                                       | Yes      |
| FM approval                                       | Yes      |
| RCM (formerly C-TICK)                             | Yes      |
| KC approval                                       | Yes      |
| EAC (formerly Gost-R)                             | Yes      |
| CCC   | Yes      |
| Ambient conditions                                |          |
| Ambient temperature during operation              |          |
| • min.  | 0 °C     |
| • max.  | 60 °C    |
| Ambient temperature during storage/transportation |          |
| • min.  | 0 °C     |
| • max.  | 70 °C    |
| Mechanics/material                                |          |
| rack profile material                             | aluminum |
| Dimensions  |          |
| Width   | 482.5 mm |
| Height  | 290 mm   |
| Depth   | 27.5 mm  |
| Weights   |          |
| Weight, approx.                                   | 3 kg     |

last modified: 2/20/2023