## SIEMENS

## Data sheet

## 6ES7321-1BL00-0AA0



SIMATIC S7-300, Digital input SM 321, Isolated 32 DI, 24 V DC, 1x 40-pole

And the second sec	
Supply voltage	
Load voltage L+	
Rated value (DC)	24 V
<ul> <li>permissible range, lower limit (DC)</li> </ul>	20.4 V
<ul> <li>permissible range, upper limit (DC)</li> </ul>	28.8 V
Input current	
from backplane bus 5 V DC, max.	15 mA
Power loss	
Power loss, typ.	6.5 W
Digital inputs	
Number of digital inputs	32
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	32
— up to 60 °C, max.	16
vertical installation	
— up to 40 °C, max.	32
Input voltage	
<ul> <li>Type of input voltage</li> </ul>	DC
<ul> <li>Rated value (DC)</li> </ul>	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	13 to 30V
Input current	
<ul> <li>for signal "1", typ.</li> </ul>	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	1.2 ms
— at "0" to "1", max.	4.8 ms
— at "1" to "0", min.	1.2 ms
— at "1" to "0", max.	4.8 ms
Cable length	
<ul> <li>shielded, max.</li> </ul>	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	

No	
No	
No	
No	
Diagnostics indication LED	
Yes	
Potential separation	
No	
16	
Yes; Optocoupler	
500 V DC	
40-pin	
40 mm	
125 mm	
120 mm	
260 g	

last modified:

12/16/2020 🖸