

Product datasheet

Specifications



iC60N - miniature circuit breaker - 3P - 20A - C curve

A9F74320

Main

| | |
|---------------------------|---|
| Device Application | Distribution |
| Range | Acti9 |
| Product Name | Acti9 iC60 |
| Product Or Component Type | Miniature circuit-breaker |
| Device Short Name | IC60N |
| Poles Description | 3P |
| Number Of Protected Poles | 3 |
| [In] Rated Current | 20 A |
| Network Type | AC DC |
| Trip Unit Technology | Thermal-magnetic |
| Curve Code | C |
| Breaking Capacity | 6000 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1 36 kA Icu at 12...60 V AC 50/60 Hz conforming to EN/IEC 60947-2 10 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 20 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 6 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 36 kA Icu at 100...133 V AC 50/60 Hz conforming to EN/IEC 60947-2 10 kA Icu at <= 180 V DC conforming to EN/IEC 60947-2 |
| Utilisation Category | Category A conforming to EN 60947-2 Category A conforming to IEC 60947-2 |
| Suitability For Isolation | Yes conforming to EN 60898-1 Yes conforming to EN 60947-2 Yes conforming to IEC 60898-1 Yes conforming to IEC 60947-2 |
| Standards | EN 60947-2 EN 60898-1 IEC 60947-2 IEC 60898-1 |

Complementary

| | |
|-------------------------|-----------------|
| Network Frequency | 50/60 Hz |
| Magnetic Tripping Limit | 8 x In +/- 20 % |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|--|
| [Ics] Rated Service Breaking Capacity | 15 kA 75 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz 7.5 kA 75 % conforming to EN 60947-2 - 380...415 V AC 50/60 Hz 4.5 kA 75 % conforming to EN 60947-2 - 440 V AC 50/60 Hz 15 kA 75 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz 7.5 kA 75 % conforming to IEC 60947-2 - 380...415 V AC 50/60 Hz 4.5 kA 75 % conforming to IEC 60947-2 - 440 V AC 50/60 Hz 27 kA 75 % conforming to IEC 60947-2 - 12...133 V AC 50/60 Hz 27 kA 75 % conforming to EN 60947-2 - 12...133 V AC 50/60 Hz 6000 A 100 % conforming to EN 60898-1 - 400 V AC 50/60 Hz 6000 A 100 % conforming to IEC 60898-1 - 400 V AC 50/60 Hz 10 kA 100 % conforming to IEC 60947-2 - 125...180 V DC 10 kA 100 % conforming to EN 60947-2 - 125...180 V DC |
| Limitation Class | 3 conforming to EN 60898-1 3 conforming to IEC 60898-1 |
| [Ui] Rated Insulation Voltage | 500 V AC 50/60 Hz conforming to EN 60947-2 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV conforming to EN 60947-2 6 kV conforming to IEC 60947-2 |
| Contact Position Indicator | Yes |
| Control Type | Toggle |
| Local Signalling | Trip indicator |
| Mounting Mode | Fixed |
| Mounting Support | DIN rail |
| Comb Busbar And Distribution Block Compatibility | Top or bottom: YES |
| 9 Mm Pitches | 6 |
| Height | 85 mm |
| Width | 54 mm |
| Depth | 78.5 mm |
| Net Weight | 0.375 kg |
| Colour | White |
| Mechanical Durability | 20000 cycles |
| Electrical Durability | 10000 cycles |
| Connections - Terminals | Single terminal (top or bottom) 1...25 mm ² rigid Single terminal (top or bottom) 1...16 mm ² flexible |
| Wire Stripping Length | 14 mm for top or bottom connection |
| Tightening Torque | 2 N.m top or bottom |
| Earth-Leakage Protection | Separate block |

Environment

| | |
|--|---|
| Ip Degree Of Protection | IP20 conforming to IEC 60529 IP20 conforming to EN 60529 |
| Pollution Degree | 3 conforming to EN 60947-2 3 conforming to IEC 60947-2 |
| Overvoltage Category | IV |
| Tropicalisation | 2 conforming to IEC 60068-1 |
| Relative Humidity | 95 % at 55 °C |
| Operating Altitude | 0...2000 m |
| Ambient Air Temperature For Operation | -35...70 °C |
| Ambient Air Temperature For Storage | -40...85 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 5.4 cm |
| Package 1 Width | 7.5 cm |
| Package 1 Length | 9.5 cm |
| Package 1 Weight | 338 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 4 |
| Package 2 Height | 8 cm |
| Package 2 Width | 9.5 cm |
| Package 2 Length | 22.5 cm |
| Package 2 Weight | 1.462 kg |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 44 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 16.519 kg |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 12 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Product

Certifications & Standards

| | |
|--------------------------|---|
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |